

FRAC PUMP

TRIPLEX



SKID MOUNTED FRAC PUMP 2250 BHP

ENGINE



CUMMINS QSK45-C 2250HP @ 1900 RPM

TRANSMISSION



ALLISON S9810



TRIPLEX PUMP



GD HD 2250 TRIPLEX

FLUID END : 4,5" – 5,5"

DISCHARGE CONNECTION: FIG.1502-3" F

SUCTION CONNECTION: ACCORDING TO CUSTOMER REQUIREMENTS.

CONTROL SYSTEM AND INSTRUMENTATION

CONTROL ENCLOSURE/PANEL WITH LOCAL AND REMOTE CONTROL

DIMENSIONS



WEIGHT : 24.500 KG

LENGTH : 8.060 MM

WIDTH : 2.470 MM

HEIGHT : 3.100 MM

OPTIONAL

(ATEX) REMOTE CONTROL

CENTRIFUGAL PUMP

EXTRA DIESEL TANK



FRAC PUMP

QUINTUPLEX



TRAILER MOUNTED FRAC PUMP 2500 BHP

ENGINE



MTU 12V4000 S83, RATED 2500 BHP

TRANSMISSION



ALLISON 9832I



QUINTUPLEX PUMP



SPM QWS2500


FLUID END : 4.5"

DISCHARGE CONNECTION: FIG.1502-3" F.

SUCTION CONNECTION: 2 x 4" FIG 206 WINGED CONNECTIONS

CONTROL SYSTEM AND INSTRUMENTATION

PRIME WSI CONTROLS



DIMENSIONS



WEIGHT : 30.000 KG

LENGTH : 12.500 MM

WIDTH : 2.550 MM

HEIGHT : 4.000 MM

KING PIN HEIGHT : 1.400MM

OPTIONAL

(ATEX) REMOTE CONTROL

CENTRIFUGAL PUMP

EXTRA DIESEL TANK



FRAC PUMP

TRIPLEX



TRAILER MOUNTED FRAC PUMP 2250 BHP

ENGINE



MTU 12V4000 S83, RATED 2250 BHP

TRANSMISSION



ALLISON S9820

TRIPLEX PUMP



SPM TWS 2250 TRIPLEX



FLUID END : 4.5" AND 5,5"



DISCHARGE CONNECTION: FIG.1502-3" F.



SUCTION CONNECTION: 2 x 4" FIG 206 WINGED CONNECTIONS



CONTROL SYSTEM AND INSTRUMENTATION



ELECTRICAL JUNCTION BOX, INDICATING DEVICES : ENGINE'S HOUR METER, COOLANT, GEAR OIL, LUBRICATION OIL TEMPERATURE INDICATORS, PRESSURE GAUGES FOR ENGINE OIL, GEAR OIL, TACHOMETER, PRESSURE TRANSMITTER 0-15K PSI

DIMENSIONS



WEIGHT : 28.000 KG



LENGTH : 13.100 MM




WIDTH : 2.550 MM



HEIGHT : 3.850 MM

KING PIN HEIGHT : 1.350MM

OPTIONAL



CENTRIFUGAL PUMP



EXTRA DIESEL TANK

